Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 08/17/2015 Date of issue: 08/17/2015

## **SECTION 1: IDENTIFICATION**

## 1.1. Product Identifier

Product Form: Aerosol Cleaner

Product Name: True Brand Throttle Body Cleaner

Product Part #: T2006

## **1.2.** Intended Use of the Product

Use of the substance/mixture: Automotive

## 1.3. Name, Address, and Telephone of the Responsible Party

### Company

Solid Start 3705 HWY 98 South Lakeland, FL 33812 863-937-9297

www.solidstart.biz

## 1.4. Emergency Telephone Number

**Emergency Number** 

: 813-248-0585 ChemTel

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

Classification (GHS-US)	
Flam. Aerosol 2	H220
Acute Tox. 4 (Oral)	H302
Skin Irrit. 2	H315
Eye Dam. 2	H318
STOT SE 3	H336
Asp. Tox. 2	H304
Gases Under Pressure	Compressed Gas

### Full text of H-phrases: see section 16

### 2.2. Label Elements

## GHS-US Labeling

Hazard Pictograms (GHS-US)



Version: 1.0

Precautionary Statements (GHS-US): P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials No smoking. P261 - Avoid breathing vapors, mist, or spray. P264 - Wash hands, forearms, and other exposed areas thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, and eye protection. P301+P310 - If swallowed: Call a poison center or doctor. P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell. P302+P352 - If on skin: Wash with plenty of water. P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.	Signal Word (GHS-US) Hazard Statements (GHS-US)	<ul> <li>Danger</li> <li>H225 - Highly flammable liquid and vapor.</li> <li>H302 - Harmful if swallowed.</li> <li>H304 - May be fatal if swallowed and enters airways.</li> <li>H315 - Causes skin irritation.</li> <li>H318 - Causes serious eye damage.</li> <li>H336 - May cause drowsiness or dizziness.</li> </ul>
	Precautionary Statements (GHS-US)	<ul> <li>incompatible materials No smoking.</li> <li>P261 - Avoid breathing vapors, mist, or spray.</li> <li>P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.</li> <li>P270 - Do not eat, drink or smoke when using this product.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P280 - Wear protective gloves, protective clothing, and eye protection.</li> <li>P301+P310 - If swallowed: Immediately call a poison center or doctor.</li> <li>P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.</li> <li>P302+P352 - If on skin: Wash with plenty of water.</li> <li>P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position</li> </ul>

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center or doctor.
- P321 Specific treatment (see section 4 on this SDS).
- P330 Rinse mouth.
- P331 Do NOT induce vomiting.
- P362 Take off contaminated clothing and wash it before reuse.
- P370+P378 In case of fire: Use appropriate media (see section 5) to extinguish.
- P391 Collect spillage.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local, regional, national, and international regulations.
- P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

### 2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1. Substance
- Not applicable
- 3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Acetone	(CAS No) 67-64-1	60 - 90	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Carbon Dioxide	(CAS No) 124-38-9	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Asp. Tox. 1, H304
Toluene	(CAS No) 108-88-3	3 - 11	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 2, H401
Methyl Alcohol	(CAS No) 67-56-1	0 - 1	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 1B, H360 STOT SE 3, H335

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret. Full text of H-phrases: see section 16

## **SECTION 4: FIRST AID MEASURES**

### 4.1. Description of First Aid Measures

**First-aid Measures General**: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation**: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact**: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

**First-aid Measures After Eye Contact**: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**First-aid Measures After Ingestion**: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Causes skin irritation. May cause drowsiness and dizziness. Harmful if swallowed. Causes serious eye damage. May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

### 5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Combustible liquid.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion.

### 5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection. **Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

## 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures**: Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges. Do not breathe vapor, mist or spray.

### 6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Section 8, Exposure controls and personal protection and Section 13, Disposal considerations.

## SECTION 7: HANDLING AND STORAGE

## 7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist or spray. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

#### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

## 7.3. Specific End Use(s)

Automotive

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

Acetone (67-64-1)			
USA ACGIH	ACGIH TWA (ppm)	500 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>	
USA NIOSH	NIOSH REL (TWA) (ppm)	250 ppm	
USA IDLH	US IDLH (ppm)	2500 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	1800 mg/m <sup>3</sup>	
USA OSHA	OSHA PEL (TWA) (ppm)	750 ppm	
Carbon Dioxi	de (124-38-9)		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	125 mg/m <sup>3</sup>	
USA ACGIH	ACGIH TWA (ppm)	5000 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	9000 mg/m <sup>3</sup>	
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm	
USA IDLH	US IDLH (ppm)	40000 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	9000 mg/m <sup>3</sup>	
USA NIOSH	NIOSH REL (TWA) (ppm)	5000 ppm	
Toluene (108	Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>	
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm	
USA IDLH	US IDLH (ppm)	500 ppm	
USA OSHA	OSHA PEL (TWA) (mg/m³)	375 mg/m <sup>3</sup>	
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm	
Methyl Alcohol (67-56-1)			
USA ACGIH	ACGIH TWA (ppm)	000 ppm	
USA ACGIH	ACGIH STEL (ppm)	250 ppm	
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>	
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	200 ppm	

6000 ppm

260 mg/m<sup>3</sup>

200 ppm

**USA IDLH** 

**USA OSHA** 

**USA OSHA** 

US IDLH (ppm)

OSHA PEL (TWA) (mg/m<sup>3</sup>)

OSHA PEL (TWA) (ppm)

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 8.2. Exposure Controls Appropriate Engineering Controls

o.z. Exposure controls	
Appropriate Engineering Controls Personal Protective Equipment	<ul> <li>Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.</li> <li>Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear</li> </ul>
	respiratory protection. Face shield.
Materials for Protective Clothing	: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant
	clothing.
Hand Protection	: Wear protective gloves.
Eye Protection	: Chemical goggles or face shield.
Skin and Body Protection Respiratory Protection	<ul><li>Wear suitable protective clothing.</li><li>In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure</li></ul>
Respiratory Protection	levels are not known wear approved respiratory protection.
Other Information	: When using, do not eat, drink or smoke.
SECTION 9: PHYSICAL AND CHEMIC	
9.1. Information on Basic Physical	and Chemical Properties
Physical State	: Aerosol
Appearance	: Clear
Odor	: Solvent
Odor Threshold	: No data available
рН	: N/A
Evaporation Rate	: 6
Melting Point	<sup>:</sup> -95°C / -139°F
Boiling Point	: 56°C / 133°F
Flash Point	<sup>:</sup> -18°C / 0°F
Auto-ignition Temperature	<sup>:</sup> 465°C / 869°F
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: 2 (AIR = 1)
Relative Density	: No data available
Solubility	: No data available
Deutition Coofficients N. Octorel /Mator	

No data availableNo data available

**9.2. Other Information:** No additional information available

## SECTION 10: STABILITY AND REACTIVITY

**Partition Coefficient: N-Octanol/Water** 

**10.1. Reactivity:** Stable under recommended storage conditions

10.2. Chemical Stability: Stable under recommended storage conditions

**10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

Viscosity

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**10.4.** Conditions to Avoid: Direct sunlight. Extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

**10.5.** Incompatible Materials: Strong acids, strong bases, strong oxidizers.

**10.6.** Hazardous Decomposition Products: None known based on information supplied.

## SECTION 11: TOXICOLOGICAL INFORMATION

### **11.1.** Information on Toxicological Effects

Acute Toxicity: Oral: Harmful if swallowed.

Acetone (67-64-1)		
LD50 Oral Rat	5800 mg/kg	
LC50 Inhalation Rat	50100 mg/m <sup>3</sup> 8h	
LD50 Dermal Guinea pig	7426 mg/kg	
Carbon Dioxide (124-38-9)		
LD50 Oral Rat	-	
LD50 Dermal Rabbit	-	
LC50 Inhalation Rat	-	
Toluene (108-88-3)		
LD50 Oral Rat	636 mg/kg	
LD50 Dermal Rabbit	8390 mg/kg	
LC50 Inhalation Rat	26700 ppm/1h	
Methyl Alcohol (67-56-1)		
LD50 Oral Rat	5628 mg/kg	
LD50 Dermal	-	
LC50 Inhalation Rat	18 g/m³ (Exposure time: 4 h)	

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Toluene (108-88-3)	
IARC group	3

**Reproductive Toxicity:** Product is or contains a chemical or chemicals which is/are (a) known or suspected reproductive hazard(s): Toluene (CAS#108-88-3). May impair fertility. May cause harm to the unborn child. May cause harm to breastfed babies.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

**Specific Target Organ Toxicity (Repeated Exposure):** May cause disorder and damage to the : Eyes, Central nervous system, Reproductive system, Respiratory system, Liver, Kidney.

Aspiration Hazard: May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms.

Symptoms/Injuries After Skin Contact: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

## SECTION 12: ECOLOGICAL INFORMATION

Ecology - General	: Toxic to aquatic life with long lasting effects.
Acetone (67-64-1)	
LC50 Fish	<ul> <li>4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L</li> <li>LC50 static 8300: 96 h Lepomis macrochirus mg/L LC5079.6 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])</li> </ul>
EC 50 Crustacea	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)	
LC50 Fish	11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 5.89 -
	7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 50.87 - 70.34: 96 h Poecilia reticulata
	mg/L LC50 static 12.6: 96 h Pimephales promelas mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static
	5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 54: 96 h Oryzias latipes mg/L LC50 static
EC50 Algea plants	12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 433: 96 h Pseudokirchneriella subcapitata mg/L EC50
EC 50 Crustacea	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
Methyl Alcohol (67-56-1)	
LC50 Fish 1	13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus
	mykiss mL/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow- through 28200:
	96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static

## 12.2. Persistence and Degradability

True Brand Throttle Body Cleaner	
Persistence and Degradability	Readily biogradable in water, soil under anaerobic conditions

## 12.3. Bioaccumulative Potential

True Brand Throttle Body Cleaner	
Bioaccumulative Potential	Bioaccumulative potenial

12.4. Mobility in Soil: No additional information available

## 12.5. Other Adverse Effects

**Other Information** 

: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

## 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

## 14.1. In Accordance with DOT

Proper Shipping Name : UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY

## 14.2. In Accordance with IMDG

Proper Shipping Name : UN1950, AEROSOLS, 2

## 14.3. In Accordance with IATA

Proper Shipping Name : UN1950, AEROSOLS, FLAMMABLE, 2.1

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 15: REGULATORY INFORMATION

True Brand Throttle Body Cleaner	
SARA Section 311/312 Hazard Classes	Fire hazard
	Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	1.0 %
Acetone (67-64-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule
	under TSCA.

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision Date</b>	

: 08/17/2015

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

### **GHS Full Text Phrases**:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)